versatile™ 4C Mailbox, 4C16S-14 → 17½" ACTUAL |-16¹/₄" R.O. 561/2" 55%16" R.O. ACTŪAL 67" (TO TENANT LOCK) (TO ACCESS DOOR LOCK) 15" 141/8" (TO BOTTOM FROM FINISHED FLOOR SHELF) TO BOTTOM OF R.O.

FINISHED FLOOR

COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
MAILBOX	MB1	3" H x 12" W x 15" D	14
OUTGOING MAIL	OM1	3" H x 12" W x 15" D	1

Notes:

- 1. This module does NOT meet USPS STD-4C installation specification requirements because there are customer compartments (interior bottom shelf) positioned less than 28" AFF.
- 2. This 4C mailbox can be used for private applications.
- 3. The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths) 1%".

PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX

MODEL 4	C16S-14	REV	D
SCALE	NONE	LAS	t rev date 1/04/2019
DRAWING	NUMBER		DRAWN BY
4C	16S-14CS		SDH