


Versatile™ 4C Mailbox, 4C15S-13



COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
MAILBOX	MB1	3" H X 12" W X 15" D	13
OUTGOING MAIL	OM2	6-1/2" H X 12" W X 15" D	1

PRODUCT SERIES: VERSATILE™ 4C FRONT LOAD MAILBOX

The Mailbox Works

1743 Quincy Ave. Suite 151

Naperville, IL 60540

800-824-9985

www.MailboxWorks.com

MODEL	REV	REV
4C15S-13	D	
SCALE	NONE	LAST REV DATE
		5/15/14
DRAWING NUMBER	4C15S-13CS	DRAWN BY
		RS

Notes:

- This module does NOT meet USPS STD-4C installation specification requirements as shown below:
 - At least one customer compartment shall be positioned less than 48" above finished floor (AFF).
 - No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - No patron (tenant) lock shall be positioned more than 67" AFF.
 - No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - The USPS Arrow lock shall be positioned 36" - 48" AFF.
- This 4C mailbox is to be used for private applications.
- The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths) - 1/8".